

AD-A083 891

FOREIGN TECHNOLOGY DIV WRIGHT-PATTERSON AFB OH  
HARD POLYURETHANE AND THE PROCESS TO OBTAIN IT.(U)  
MAR 80

F/G 11/9

UNCLASSIFIED

FTD-ID(RS)T-0170-80

NL

1 OF 1  
AD-A083 891



END  
DATE  
FILMED  
6-80  
DTIC

2

FTD-ID(RS)T-0170-80


ADA083891

# FOREIGN TECHNOLOGY DIVISION



HARD POLYURETHANE AND THE  
PROCESS TO OBTAIN IT

DTIC  
ELECTE  
MAY 5 1980  
S B D



Approved for public release;  
distribution unlimited.

FILE COPY

80 4 17 117

## EDITED TRANSLATION

(14) FTD-ID(RS)T-0170-80 (11) 28 Mar 1980 (12) 4

CSB79167238 FTD-80-C-000401

(6) HARD POLYURETHANE AND THE  
PROCESS TO OBTAIN IT.

English pages: 2 *2D Editor Trans.*

Source: Revista de Chimie, Nr. 3,  
March 1978, *Mar 78, p. 213*

Country of origin: (Romania) *v27 n3 p213 Mar 78, C.A.*  
Translated by: Linguistic Systems, Inc.  
F33657-78-D-0618  
Mina Winters.

Requester: FTD/PHE  
Approved for public release;  
distribution unlimited.

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:

TRANSLATION DIVISION  
FOREIGN TECHNOLOGY DIVISION  
WP-AFB, OHIO.

FTD -ID(RS)T-0170-80

Date 28 Mar 1980

14160

out

JOURNAL OF CHEMISTRY

\* CHEMISTRY

\* CHEMICAL ENGINEERING

\* CHEMICAL EQUIPMENT

Volume 29, March 1978, pages 197 - 288

Central Institute of Chemistry, Bucharest, Romania

#### Patents

Hard polyurethane and the process to obtain it  
(Poliuretan dur și procedeu de obținere a acestuia)

The Socialist Republic of Romania Patent Number 56149

The invention refers to the hard polyurethane and the process to obtain it.

The hard polyurethane has a block-copolymer structure of polyester-polyurethane, and is obtained through the solubilization in a first stage of about 6 mols 4.4'-dibenzyl-diisocyanate as a diisocyanic component in 1 mol poly(ethylenglycoladipat) with a molecular weight of about 2,000; in a second phase, the product of the reaction is treated with 4.5 mols of glycoles and the fluid mass of the reaction is poured into moulds; the finishing takes place at 120°C.

The invention presents the following advantages:

- it uses an easily accessible diisocyanate;
- it extends the period of gellification, which enables a comfortable processing;

- the polyurethane obtained presents superior physical and mechanical properties.

File number 61753

Int. cl<sup>2</sup>: C08 G71/04

Registration date: 12/4/1969

Publication date: 10/1/1977

Holder of Title: The Institute of Macromolecular Chemistry  
"Petru Poni", Iași.

ACCESSION for	
NTIS	White Section <input checked="" type="checkbox"/>
DDC	Buff Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist. AVAIL. and/or SPECIAL	
A	